

## NOTES:

- 1. SETTER TO BE PLACED IN PIT THAT IS 30" IN DIAMETER OR LARGER, SEE DETAIL W6.16.
- 2. ELECTRONIC METER READING COVER WITH REMOVABLE PLUG. MANUFACTURER FORD OR COUNTY APPROVED EQUAL.
- 3. METER SETTING SHOULD NOT BE INSTALLED IN DRIVEWAY, SIDEWALK, OR PAVED/CONCRETE AREAS.
- 4. DUAL CHECK VALVE WILL BE INSTALLED AS SPECIFIED UNDER UTILITY PERMIT AND MUST BE STAMPED ASSE 1024.
- 5. IF FIRE SPRINKLER SYSTEM IS NOT A STANDARD DOMESTIC WATER FIRE SUPRESSION SYSTEM IN ACCORDANCE WITH CROSS CONNECTION CONTROL BILL 2005—20, AN ASSE 1013 REDUCED PRESSURE ZONE BACKFLOW ASSEMBLY IS REQUIRED.

6. USE METER YOKE FORD #Y-502 (5/8" METER), 503 (3/4" METER), OR 504 (1" METER) AS SPECIFIED.

CHARLES COUNTY GOVERNMENT	STANDARD DETAIL	REVISIONS:	
APPROVED:  CHIEF OF DEVELOPMENT SERVICES DATE  1-18-07  WATER SEWER ENGINEER DATE	INGROUND METER SETTING HOMES WITH FIRE SPRINKLER SYSTEMS – 5/8", 3/4", & 1" METER – 1" FIRE SPRINKLER LINE		W 6.15